

osCommerce, , , , , , , , ,
, DEBUG.

PHP
orders_total account.php

```
$orders_query = tep_db_query("select o.orders_id, o.date_purchased, o.delivery_name, o.delivery_country, o.billing_name, o.billing_country, ot.text as order_total, s.orders_status_name from " . TABLE_ORDERS . " o, " . TABLE_ORDERS_TOTAL . " ot, " . TABLE_ORDERS_STATUS . " s where o.customers_id = " . (int)$customer_id . " and o.orders_id = ot.orders_id and ot.class = 'ot_total' and o.orders_status = s.orders_status_id and s.language_id = " . (int)$languages_id . " order by orders_id desc limit 3");
```

```
o.orders_id = ot.orders_id and ot.class check out_process.php
```

```
for ($i=0, $n=sizeof($order_totals); $i < $n; $i++) {  
    'title' => $order_totals[$i]['title'],  
    'text' => $order_totals[$i]['text'],  
    'value' => $order_totals[$i]['value'],  
    'class' => $order_totals[$i]['code'],  
    'sort_order' => $order_totals[$i]['sort_order'];  
    tep_db_perform(TABLE_ORDERS_TOTAL, $sql_data_array);  
  
}
```

```
$order_totals  
LINUX WINDOWS
```